

SCALEOVIEW L22W-13

22 Inch LCD widescreen Display

Issue May 2008

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L22W-13 widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L22W-13 fits perfectly into your home environment.

Highlights

- \$ 22-inch widescreen display for a perfect viewing experience at high resolution
- \$ Best performance to an affordable price
- \$ Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- \$ Optimum flicker-free and distortion-free picture
- \$ Excellent colour purity
- \$ Well balanced brightness uniformity
- \$ Excellent high contrast (3000:1)
- \$ Space saving design

Technical highlights

- \$ 22" (55.9 cm) LCD widescreen display
- \$ Excellent contrast 3000:1
- \$ Brightness 300 cd/m²
- \$ Fast response time (typ.) 5 ms
- \$ Internal power supply

Reliability

- \$ Low power consumption
- \$ Power management according to EPA
- \$ Guaranteed quality and stability



Visible screen diagonal	22 inch (55.9 cm)
Resolutions	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
Picture size	473.76 x 296.1 mm
Colours	16.2 million
Pixel Pitch	0.282 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Brightness (typical)	300 cd/m²
Contrast (ACR)	3000:1
Viewing angle (typical)	CR>5
Horizontal	170°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, Spanish, French, Italian, Russian, Polish, Dutch	
Base	
Tilt angle	-5°/ +20°
Audio characteristics	
Audio signal input	3.5mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw	
Max.	<49 W
Stand by	< 2 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (W x H x D):	
(with stand)	515 x 415 x 206 mm
Weight (Monitor only)	5,4 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and	CE certification according
RFI suppression	to EC Directive
	2004/108/EEC
	(EN55022/B, EN55024
	EN61000-3-2/-3);
	TCO'03
Ecology	RoHS, IT-Eco-declaration,
	Energy Star (EPA 4.1)
Video input	1 x D-SUB
Accessories	
2 x Power cable (1.5 m)*	1 x wall socket
	(Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	
Special features	Standardized mounting
	interface according
	VESA FPMPI (100 mm)
	Kensington Lock
Order code	S26361-K1288-V205
EAN	4333643559960